



Representative Photo Only
(actual product may vary based on configuration selections)

MicroLogix Digital Output Module 16 Point V AC/V DC Relay

- Feature-rich functionality addresses a wide range of application
- Software keying prevents incorrect positioning within the syste
- Finger-safe terminal blocks for I/O wiring
- Small footprint reduces panel space

SPECIFICATIONS

Product Series	MicroLogix Expansion I/O (Bul. 1762)
Component Type PLC & I/O	Digital Output Module
Number of Digital Outputs	16 qty
Digital Output Type	AC/DC NO Contact type
Digital Output Range	5...264V AC / 5...125V DC
Rated Current per Digital Output, Max	2.5 A max, per DO
Rated Current per Module, Max	16 A max, per module
Type, Relay Output	NO AC/DC type
Operating Temperature, Max	65 °C max
Operating Temperature, Min	-20 °C min
Relative Humidity, Max	95 %RH
Shock Acceleration (Max.)	30 g
Vibration Acceleration (Max.)	5 m/s²
Vibration Displacement (Peak to Peak Max.)	0.381 mm
Vibration Frequency, Operational (Max.)	500 Hz

REFERENCES

IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-