


WAZ4 PRO DC/DC**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Similar to illustration****Product is no longer available****General ordering data**

Version	Signal converter/insulator, Tension-clamp connection
Order No.	8560750000
Type	WAZ4 PRO DC/DC
GTIN (EAN)	4032248207367
Qty.	1 pc(s).
Delivery status	Discontinued
Available until	2018-01-31
Alternative product	1481960000

Creation date May 28, 2025 8:26:37 AM CEST

Catalogue status 24.05.2025 / We reserve the right to make technical changes.

WAZ4 PRO DC/DC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	112.4 mm	Depth (inches)	4.425 inch
Width	12.5 mm	Width (inches)	0.492 inch
Length	92.4 mm	Length (inches)	3.638 inch
Net weight	162.8 g		

Temperatures

Storage temperature	-40 °C...85 °C	Operating temperature	-10 °C...70 °C
---------------------	----------------	-----------------------	----------------

Probability of failure

MTTF	76 a
------	------

Input

Input current	configurable, $\pm 0.1 \text{ mA} \dots \pm 100 \text{ mA}$	Input resistance, current	< 5 mA: approx. 100 Ω ; >5 mA: approx. 5 Ω
Input resistance, voltage	approx. 1 M Ω	Input voltage	configurable, $\pm 20 \text{ mV} \dots \pm 200 \text{ V}$
Number of inputs	1		

Output

Cut-off frequency (-3 dB)	> 10 kHz / < 10 Hz	Load impedance current	$\leq 600 \Omega$
Number of outputs	1	Offset current	20 μA
Offset voltage	10 mV	Output current	0... $\pm 20 \text{ mA}$
Output voltage, note	0... $\pm 10 \text{ V}$	load impedance voltage	$\geq 1 \text{ k}\Omega$

General data

Accuracy	< 0.1 % of end value, + Offset 0.1 %	Configuration	DIP switch and potentiometer, with reference voltage/current sources
Galvanic isolation	3-way isolator	Power consumption	ca. 1 W
Protection degree	IP20	Rail	TS 35
Step response time	120 μs at limiting-frequency setting > 10 kHz, 75 ms at limiting-frequency setting < 10 Hz	Temperature coefficient	$\leq 60 \text{ ppm/K}$ of final value
Voltage supply	22...230 V AC/DC +10 %		

Insulation coordination

EMC standards	DIN EN 61326, EN 61000-2-6, EN 61709 (SN 29500) MTBF	Galvanic isolation	3-way isolator
Impulse withstand voltage	5 kV, 1.2/50 μs (IEC 255-4)	Insulation voltage	4 kV _{eff}
Insulation voltage input or output/rail	4 kV _{eff}	Insulation voltage input or output/supply	4 kV _{eff}
Pollution severity	2	Rated voltage	600 V
Surge voltage category	III		

WAZ4 PRO DC/DC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Connection data

Type of connection	Tension-clamp connection	Stripping length, rated connection	7 mm
Clamping range, rated connection	1.5 mm ²	Clamping range, min.	0.5 mm ²
Clamping range, max.	2.5 mm ²		

Classifications

ETIM 6.0	EC002653	ETIM 7.0	EC002653
ETIM 8.0	EC002653	ETIM 9.0	EC002653
ETIM 10.0	EC002653	ECLASS 9.0	27-21-01-20
ECLASS 9.1	27-21-01-20	ECLASS 10.0	27-21-01-20
ECLASS 11.0	27-21-01-20	ECLASS 12.0	27-21-01-20
ECLASS 13.0	27-21-01-20	ECLASS 14.0	27-21-01-20
ECLASS 15.0	27-21-01-20		

WAZ4 PRO DC/DC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Tender specification sheets

Long specification

Add-on housing for
TS35 rail mounting
Dimensions: L/W/H
92.4/ 12.5/ 112.4 mm
Tension-clamp connec-
tion/ Nominal cross-
section 1.5 mm²
Protection degree: IP
20
Input +/-
20mV.../- 200 V, +/- 0,1
mA.../- 100 mA
Out-
put
0 ... +/- 10 V, 0... +/- 20
mA
Selection
range
calibrated selection
with DIP switches/ 440
ranges
Front-side calibration
with zero/span poten-
tiometer
Transmission er-
ror < 0,2% v. E.
Limit frequency 10 Hz /
10 kHz adjustable
Auxiliary pow-
er
22...230 V AC/DC +/-
10%
Power loss approx. 1 W
Ambient
temperature range -10
°C...+70 °C

Secure isola-
tion EN 50178,
3-way isolation up to 4
kV AC/DC of all circuits
against each other
Test volt-
age 4
kV, 50 Hz input against
output against auxiliary
power
Rated voltage 5 kV,
1.2/50 us
Working volt-
age 600 V
AC/DC at overvoltage
category III and pollu-
tion degree 2
Approvals cULus, GL

Type
WAZ4 PRO DC/DC

Short specification

Standard signal iso-
lating converter, Ze-
ro/span compensation,
calibrated selection 1-
 channel signal isolating
 converter: with 12.5 mm
 width and external power
 supply for transmitting and
 isolating analogue DC cur-
 rent (± 0.1 to ± 100 mA)
 and voltage signals.

WAZ4 PRO DC/DC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Environmental Product Compliance

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	7a, 7cl
REACH SVHC	Lead 7439-92-1
SCIP	94561991-a963-4084-a5f3-dfa3a5c2a27e

Approvals

Approvals



Approvals MAMID	https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/ https://mdcop.weidmueller.com/mediadelivery/rendition/900_319228/-T1z1mm-S800/ https://mdcop.weidmueller.com/mediadelivery/rendition/900_322323/-T1z1mm-S800/ https://mdcop.weidmueller.com/mediadelivery/rendition/900_319225/-T1z1mm-S800/
-----------------	---

ROHS	Conform
UL File Number Search	UL Website
Certificate no. (cULus)	E141197
Certificate no. (cULusEX)	E346097




Downloads

Approval/Certificate/Document of Conformity	Application notes – Declaration of Conformity
Software	Software – WaveTool.zip
User Documentation	Instruction sheet
Catalogues	Catalogues in PDF-format

WAZ4 PRO DC/DC

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Drawings
Electric symbol


Screenshot example, Wave tool software