

9002/22-032-300-111 Art. No. 158954



- For the intrinsically safe operation of a wide range of devices, such as HART transmitters, solenoid valves, sensors, zero-potential contacts and many more
- Compact, space-saving devices that are easy to install on a DIN rail
- Quick to install as barriers can be simultaneously snapped onto rail and connected to PE

WebCode **9002A**



The 9002 series INTRINSPAK two-channel safety barriers enable the intrinsically safe operation of virtually all field devices. The comprehensive portfolio and the combination of safety barriers cover a wide variety of signals. The devices are incredibly robust and require very little space. The back-up fuse is a convenient feature as it is standardised for all variants.

Technical Data

Explosion Protection

Application range (zones)	2 22
Ex interface zone	0 1 2 20 21 22
Certificate IECEX Gas	IECEX PTB 08.0057X
Certificate ATEX Gas	PTB 01 ATEX 2053 X
Certificate IECEX Dust	IECEX PTB 08.0057X
Certificate ATEX Dust	PTB 01 ATEX 2053 X
Gas explosion protection IECEX	Ex nA [ia Ga] IIC/IIB T4 Gc
Gas explosion protection ATEX	Ex II 3 (1) G Ex nA [ia Ga] IIC/IIB T4 Gc
Dust explosion protection IECEX	[Ex ia Da] IIIC
Dust explosion protection ATEX	Ex II (1) D [Ex ia Da] IIIC
Certificates	ATEX (PTB), Brazil (ULB), Canada (CSA), China (CQST), EAC (STV), IECEX (PTB), Korea (KGS), USA (FM), USA (UL)
EAC certificate	TS RU S-DE.GB04.B.00134
Installation	in Zone 2, Division 2 and in safe area

Safety Data

Max. voltage U_o	1.6 V
Max. voltage U_o	1.6 V 1.6 V 3.2 V
Max. current I_o	150 mA
Max. power P_o	60 mW
Max. permissible external capacitance C_o for IIC	100 μ F

9002/22-032-300-111 Art. No. 158954

Safety Data

Max. permissible external capacitance C_o for IIB	1000 μ F
Max. permissible external inductance L_o for IIC	1.3 mH
Max. permissible external inductance L_o for IIB	7 mH
Further information	see respective certificate and operating instructions

Electrical Data

Number of channels	2					
Channel	1 2 1 + 2					
Nominal voltage U _N	0,7 V 0.7 V 1.4 V					
Min. resistance R _{min}	19.9 Ω 19.9 Ω					
Max. resistance R _{max}	20.1 Ω 20.1 Ω					
Max. current I _o	150 mA 150 mA 300 mA					
Max. power P _o	60 mW 60 mW 120 mW					
DC rated operational voltage	0.7 V					
Power supply	Controlled, nominal voltage					
Nominal voltage	0,7 V					
Maximum resistance Rmax	20.1 Ω					
Minimum resistance Rmin	19.9 Ω					
Maximum output current Imax	33 mA					
Potential	Alternative potential					
Potential Ch 1	Alternative potential					
Potential Ch 2	Alternative potential					
Ohm.curr.lim.usingfreq.>= 50mA	≤ 100 kHz					
Ohm.curr.lim.usingfreq<= 50 mA	≤ 50 kHz					
Ileak leakage current for Un	≤ 2 μA					
Ileak leakage current for Un 2	(Unless specified otherwise)					
Channel	Nominal voltage U _N	Min. resistance R _{min}	Max. resistance R _{max}	Max. voltage U _o	Max. current I _o	Max. power P _o
1	0,70 V	19.90 Ω	20.10 Ω	1.60 V	150.0 mA	60.000 mW
2	0.70 V	19.90 Ω	20.10 Ω	1.60 V	150.0 mA	60.000 mW
1 + 2	1.40 V			3.20 V	300.0 mA	120.000 mW

Ambient Conditions

Min. ambient temperature	-20 °C
Max. ambient temperature	+60 °C

9002/22-032-300-111 Art. No. 158954

Ambient Conditions

Ambient temperature	-20 °C ... +60 °C
Min. storage temperature	-20 °C
Max. storage temperature	+75 °C
Storage temperature	-20 °C ... +75 °C
Maximum relative humidity	95% on av., no condensation
Temperature influence	≤ 0,25 %/10K



Mechanical Data

Degree of protection (IP)	IP40
Degree of protection (IP) Terminals	IP20
Enclosure material	Polyamide 6GF
Number of connection terminals	4
Max. clamping range	1.5 mm ²
Connection cross-section	4 mm ²
Type of connection cable	Solid Finely stranded
Width	103 mm
Length	12 mm
Mounting depth	72 mm
Weight	0.11 kg

Mounting / Installation


Connection type	2 PA
-----------------	------

Technical Drawings




Picture J

Two-channel safety barriers, potential: ~ / ~





Application: Pt100, 2-wire circuit, field circuit unearthed

9002/22-032-300-111 Art. No. 158954




Application: Pt100, 3-wire circuit field circuit unearthed


Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



Mounting on DIN rail NS 35/15



Mounting on DIN rail NS 32 by means of adaptor and mounting attachment, moulded plastic



Mounting on mounting plate by means of adaptor


Accessories and Spare Parts

Table with 2 columns: Accessory Name and Art. No.
Row 1: Back-up fuse, For all safety barriers Series 9001, 9002 and 9004 unit: 5 pcs., 158964
Row 2: Holder for label, Transparent cover for labelling, 158977

9002/22-032-300-111 Art. No. 158954

Labelling paper

Art. No.



Perforated, for typing
Format: DIN A4
Packaging unit: 80 pieces

158973


Adaptor

Art. No.




Adaptor allows installation of a safety barrier Series 900x on a mounting plate of a previous series.

158826



Mounting attachment moulded plastic

Art. No.




Enables mounting of safety barrier on a G-rail.

165283

DIN rail

Art. No.




NS35/15 (meter length)

103714

Earth terminal

Art. No.



USLKG 5 (wire range 4 mm²)
Terminal enables connection of protective conductors to DIN rail. Colour green-yellow.


112760

USLKG 6 N (wire range 6 mm²)
Terminal enables connection of protective / earthing conductors to DIN rail. Colour green-yellow.

112599


Fuse holder

Art. No.




Fuse holder is snapped onto the side of the safety barrier and can be equipped with up to 5 back-up fuses (replacement).

158834




Insulating stand off

Art. No.



Suitable for DIN rail NS35/15, allows electrically insulated mounting of DIN rail from mounting plate.

158828



We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.