

FLK 16 - Interface module

2280080

<https://www.phoenixcontact.com/in/products/2280080>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE module, with screw connection and flat-ribbon cable connector, for mounting on NS 32 or NS 35/7.5, with male connector and short and long locking latches for sockets, 16-pos. (separate test socket for each channel)

Commercial data

Item number	2280080
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	CK2
Product key	CK2181
Catalog page	Page 242 (IF-2007)
GTIN	4017918054335
Weight per piece (including packing)	90.73 g
Weight per piece (excluding packing)	82.936 g
Customs tariff number	85369010
Country of origin	DE

FLK 16 - Interface module

2280080

<https://www.phoenixcontact.com/in/products/2280080>



Technical data

Product properties

Product type	Interface module
Number of positions	16

Insulation characteristics

Overvoltage category	II
Pollution degree	2

Electrical properties

Nominal voltage U_N	< 50 V AC
	60 V DC
Max. current carrying capacity per branch	1 A

Connection data

PCB connection

Connection in acc. with standard	IEC / EN
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Controller level

Connection method	IDC/FLK pin strip
Number of positions	16
Pitch	2.54 mm

Signaling

Status display	No
Status display present	No

Dimensions

Item dimensions

Width	60 mm
Height	50 mm
Depth	58.5 mm

Material specifications

Color	green (RAL 6021)
Housing insulation material	Polyamide 6 green

FLK 16 - Interface module

2280080

<https://www.phoenixcontact.com/in/products/2280080>



Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Standards and regulations

Standards/regulations	IEC 60664
	DIN EN 50178

Mounting

Mounting type	DIN rail mounting
Mounting position	any

Notes

Notes on operation	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
--------------------	--

FLK 16 - Interface module


2280080

<https://www.phoenixcontact.com/in/products/2280080>



Drawings

Circuit diagram



FLK 16 - Interface module

2280080
<https://www.phoenixcontact.com/in/products/2280080>



Classifications

ECLASS

ECLASS-11.0	27141152
-------------	----------

FLK 16 - Interface module

2280080
<https://www.phoenixcontact.com/in/products/2280080>



Environmental product compliance

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

FLK 16 - Interface module

2280080

<https://www.phoenixcontact.com/in/products/2280080>



Accessories

RPS - Reducing plug

0201647

<https://www.phoenixcontact.com/in/products/0201647>



Reducing plug, number of positions: 1, color: gray

FLK EZ-DR.../.../... - Cable

2295059

<https://www.phoenixcontact.com/in/products/2295059>



Round cable, with preassembly, not shielded, variable cable length

FLK 16 - Interface module



2280080

<https://www.phoenixcontact.com/in/products/2280080>

FLK 16/EZ-DR/ 50/KONFEK - Cable

2299291

<https://www.phoenixcontact.com/in/products/2299291>



Round cable set; connection 1: IDC/FLK socket strip (1x 16-position); connection 2: IDC/FLK socket strip (1x 16-position); cable length: 0.5 m

FLK 16/EZ-DR/ 100/KONFEK - Cable

2299301

<https://www.phoenixcontact.com/in/products/2299301>



Round cable set; connection 1: IDC/FLK socket strip (1x 16-position); connection 2: IDC/FLK socket strip (1x 16-position); cable length: 1 m

FLK 16 - Interface module



2280080

<https://www.phoenixcontact.com/in/products/2280080>

FLK 16/EZ-DR/ 150/KONFEK - Cable

2299314

<https://www.phoenixcontact.com/in/products/2299314>



Round cable set; connection 1: IDC/FLK socket strip (1x 16-position); connection 2: IDC/FLK socket strip (1x 16-position); cable length: 1.5 m

FLK 16/EZ-DR/ 200/KONFEK - Cable

2299327

<https://www.phoenixcontact.com/in/products/2299327>



Round cable set; connection 1: IDC/FLK socket strip (1x 16-position); connection 2: IDC/FLK socket strip (1x 16-position); cable length: 2 m

FLK 16 - Interface module



2280080

<https://www.phoenixcontact.com/in/products/2280080>

FLK 16/EZ-DR/ 300/KONFEK - Cable

2299330

<https://www.phoenixcontact.com/in/products/2299330>



Round cable set; connection 1: IDC/FLK socket strip (1x 16-position); connection 2: IDC/FLK socket strip (1x 16-position); cable length: 3 m

FLK 16/EZ-DR/ 400/KONFEK - Cable

2299343

<https://www.phoenixcontact.com/in/products/2299343>



Round cable set; connection 1: IDC/FLK socket strip (1x 16-position); connection 2: IDC/FLK socket strip (1x 16-position); cable length: 4 m

FLK 16 - Interface module



2280080

<https://www.phoenixcontact.com/in/products/2280080>

FLK 16/EZ-DR/ 600/KONFEK - Cable

2299356

<https://www.phoenixcontact.com/in/products/2299356>



Round cable set; connection 1: IDC/FLK socket strip (1x 16-position); connection 2: IDC/FLK socket strip (1x 16-position); cable length: 6 m

FLK 16/EZ-DR/ 800/KONFEK - Cable

2299369

<https://www.phoenixcontact.com/in/products/2299369>



Round cable set; connection 1: IDC/FLK socket strip (1x 16-position); connection 2: IDC/FLK socket strip (1x 16-position); cable length: 8 m

FLK 16 - Interface module

2280080

<https://www.phoenixcontact.com/in/products/2280080>



FLK 16/EZ-DR/1000/KONFEK - Cable

2299372

<https://www.phoenixcontact.com/in/products/2299372>



Round cable set; connection 1: IDC/FLK socket strip (1x 16-position); connection 2: IDC/FLK socket strip (1x 16-position); cable length: 10 m

FLK 16/EZ-DR/ 400/KONFEK/S - Cable

2318091

<https://www.phoenixcontact.com/in/products/2318091>



Assembled shielded round cable; connection 1: IDC/FLK socket strip (1x 16-position); connection 2: IDC/FLK socket strip (1x 16-position) (The braided shield is routed to a separate cable end.); cable length: 4 m

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in